

SANY/



SY750

# COMPACT POWERHOUSE VERSATILE AS STANDARD.

#### **CONSTRUCTION MACHINERY**



COMPACT EXCAVATORS

Engine YANMAR 4TNV98CT Rated Power 42.4 kW / 1900 rpm Bucket capacity 0.28 m<sup>3</sup> Operating mass 7280 kg

# SANY

## For challenging tasks, you need a first-class partner

Quality comes from experience. And from new ideas. This is why we combine these two crucial factors at SANY. This is because we are one of the world's leading producers, having sold more than **320000** excavators in **10 years**. This means that you can always rely on sophisticated products that have been tried and tested in practice. An impressive **5–7%** of our annual turnover is dedicated to research and development. This is why we give you not only our word, but also our extraordinary **five-year warranty** as a guarantee of how powerful and robust our products are.

## **320000** EXCAVATORS SOLD IN **10 YEARS**

**5–7%** TURNOVER FOR RESEARCH AND DEVELOPMENT

FIVE-YEAR Warranty \*

Quality Changes the World



## RAISING THE BAR IN THE COMPACT CLASS

The new SANY SY75C – powerful and with a large excavation depth, this machine completes all tasks efficiently and with a reliable performance. The excavator's sophisticated structure allows it to tackle very high loads with exemplary stability. Moreover, the cab's state-of-the-art design is reminiscent of a comfortable car interior. This is not only visually appealing to drivers – the cab's comfort and ergonomics are precisely tailored to the requirements for safe and concentrated work.



Max. bucket digging force 53 kN (ISO)

Max. arm digging force 35 kN (ISO)

Swingspeed 10.5 rpm

Max. travel speed 5.3 km/h

2820 mm

## **TOP PROPERTIES**

# COMPONENTS QUALITY TO THE LAST DETAIL

SY750

par

With

In conjunction with the exhaust treatment, the Yanmar engine always delivers a full and clean performance for every task. Its diesel particulate filter with self-regenerating coating ensures that the emission control is straightforward and performs reliably. Another benefit when it comes to durability and reliability is the that the top rollers are mounted on both side This makes them more robust, ever subjected to high st

#### **OUALITY**

Completely sealed - the driver's cab's improved seal makes it a real comfort zone, keeping out noise, dust, exhaust gases, etc.

#### **USER EXPERIENCE**

Always optimally configured - it is easy to program different attachment devices, which saves time and money when changing them. The machine's modern interior ensures maximum comfort and therefore facilitates fatique-free work. In addition, the Bluetooth interface allows operators to connect their mobile phone to the factory-fitted speakers to answer calls or play music.

#### SAFETY

Everything in sight - the protected rear camera gives an accurate image of the surrounding area. The driver can see these images on the high-resolution display directly in their field of vision.

#### COMPONENTS

Powerful and clean - the high-torque Yanmar engine delivers full power in every situation. In addition, with its tailored exhaust treatment, the machine achieves emission standard 5 without any difficulty.

SANY

#### Absolute reliability for peace of mind!

SANY

SANY's five-year warranty\* gives you the assurance that you can fully count on your equipment.





#### COMPONENTS

#### Both hard and soft

The SY75C does not have any plastic covers. This machine consists solely of high-quality steel, which is particularly robust and quick and easy to repair in case of an emergency.

Despite weighing almost 7.5 tonnes, the compact extractor is gentle on the ground with its rubber crawler tracks. This protects a wide range of surfaces from damage and makes the machine drive smoothly.





#### DIMENSIONS

Optimal design - the undercarriage and structure are perfectly coordinated. The position of the boom also means that the excavator can lift higher loads over longer reaches than comparable machines in this weight class.



#### ECONOMY

Designed for maximum efficiency - the intelligent load-sensing hydraulic system always knows precisely how much hydraulic power is required for each task and delivers precisely the amount of oil needed.

## EFFICIENCY, COST-EFFECTIVENESS AND USER EXPERIEN

#### USER EXPERIENCE

## **ON-BOARD** COMFORT

While comfort has a lot to do with convenience, it has even more to do with health and safety and facilitating fatigue-free, concentrated work. Machine operators are therefore the focus of the entire design for the driver's cab. At the forefront are the joysticks, which make particularly precise work easy, and the high-resolution 7" touch display, which impresses with its simple and intuitive menu navigation and can even be operated when wearing gloves.

Moreover, the Bluetooth interface allows users to connect their phone in order to answer calls or simply to play music.

#### USER EXPERIENCE

#### **Ouicker maintenance**

It is important to carry out routine daily checks. In spite of the machine's large dimensions, all of the areas relevant for maintenance - such as the air filter and engine oil monitoring - are arranged so that they are quickly and easily accessible from the ground.

#### USER EXPERIENCE **Optimal visibility in every respect**

The extra-large front and side windows, as well the curved rear window provide optimal visibility of the entire working environment without any areas hidden. The standard rear camera covers visibility to the rear, sending a high-resolution image to the 7" touch display. There are also easy-to-adjust sun covers, which enable glare-free work even in difficult lighting conditions.



## ECONOMY

The high-torque drive unit is particularly fuelefficient, without sacrificing any performance. The driver can simply choose the optimal operating mode for different applications. For instance, you can switch from maximum power to maximum efficiency via touch operation and this will be reflected in the fuel costs. Another feature which saves time and costs is the fact that hydraulic quick-coupler is already included ex-works as standard and is incorporated into the overall operating concept. This makes it quick and easy to change attachment devices at the construction site and neatly incorporates this function into the overall operation of the machine.





Tried-and-tested Kawasaki technology is used for the machine's hydraulics. It can deliver up to 158 litres per minute, which is sufficient even for major tasks. Depending on the application, the load-sensing hydraulic system ensures that the machine always delivers precisely the amount of hydraulic power requested by the operator.

## SAFETY

engine running.

modern equipment + Extensive programming options

Our highlights - the added

benefits SANY offers you:

for attachment devices

+ Comfortable driver's cab with

+ Rear camera

1) 65 S 1

• • • • • • • •

**V 0 8 # !!!** 

( 9.14 b

- + High-resolution 7" touch display
- + 2 proportional auxiliary control circuits on the joystick



#### **Cost-effectiveness as standard**

#### Exert a lot of pressure

#### You can rely on

SANY makes no compromises when it comes to safety. Four LED work spotlights provide the best possible illumination of the work environment, even if it starts to get dark at the construction site.

Another safety feature is the accumulator, which allows the working device to be lowered in an emergency without the

Ν	GI	N	F	

Model	YANMAR 4TNV98CT
Тур	Water-cooled, 4 cylinder, with commonrail and DPF
Exhaust emissions	Stage V
Rated power	42.4 kW / 1 900 rpm
Max. torque	241 Nm / 1 300 rpm
Displacement	3 3 19 ccm
Batteries	$1 \times 12$ V / 120 Ah

#### HYDRAULIC SYSTEM

Mainpump	Variable-piston-pump; Load sensing control
Max. oilflow	158 I/min
Travelmotor	Variable displacement axial piston motor
Swingmotor	Axial piston motor
Max. oilflow (AUX 1)	120 I/min
Max. oilflow (AUX 2)	70 l/min

#### SERVICE REFILL CAPACITIES

Fuel tank	150 I
Engine coolant	11 I
Engine oil	10.8 I
Drive (per side)	1.2
Hydraulic system	160 I
Hydraulic oil tank	120 I

#### PERFORMANCE

Swingspeed	10.5 rpm
Max. travel speed	High 5.3 km/h, slow 2.8 km/h
Max. travel force	56.8 kN
Gradeability	35°
Bucket capacity	0.28 m <sup>3</sup>
Groundpressure	0.33 kg/cm <sup>2</sup>
Bucket digging force ISO	53 kN
Arm digging force ISO	35 kN

#### RELIEF VALVE SETTINGS

Implement circuit	263 bar	
Swing circuit	240 bar	
Travle circuit	263 bar	
Pilot pressure	39 bar	

#### UNDER AND UPPER STRUCTURE

Boom length	3720 mm
Arm length	2 050 mm
Bottomrollers	5
Toprollers	1
Rotation device	Planetary gear reducer driven by an axial piston motor, automatic hydraulic released slewing brake

#### **OPERATING MASS**

SY75C

7 280 kg

#### LIFTING CAPACITIES - DOZER BLADE DOWN

•			Rac	lius			Digging	reach	
P	1.0	1.0 m		3.0 m		5.0 m		Max.	
Load point heigh	∋–€	5	∋–∄		⋗		∋—€		
6.0 m kg			1 385	1 385			1 2 1 0	1 2 1 0	
5.0 m kg							1 0 2 0	1 0 2 0	
4.0 m kg			1 315	1 3 1 5	1060	1060	950	950	
3.0 m kg			1710	1710	1460	1 225	930	930	
2.0 m kg			2275	2275	1 585	1 190	950	950	
1.0 m kg			2790	2400	1715	1 155	960	950	
Ground line kg			3085	2315	1815	1 125	1105	980	
-1.0 m kg	2105	2105	3 1 3 8	2275	1805	1 115	1 300	1070	
-2.0 m kg	3 4 1 5	3 4 1 5	2955	2280			1680	1 275	
-3.0 m kg			2 3 9 5	2340			1885	1820	

#### LIFTING CAPACITIES - DOZER BLADE UP

•		Digging reach						
	1.0 m	3.0 n	3.0 m		5.0 m		Max.	
Load point heigh	→ ,	∋⊸∄		Э—∄		∋–€		
6.0 m kg		1385 1	1 385			1 2 1 0	1 2 1 0	
5.0 m kg						1 0 2 0	1 0 2 0	
4.0 m kg		1 315	1 3 1 5	1060	1060	950	950	
3.0 m kg		1710	1710	1 310	1 225	930	930	
2.0 m kg		2275 2	2275	1 275	1 190	950	950	
1.0 m kg		2630 2	2400	1235	1 155	960	950	
Ground line kg		2540	2315	1205	1 125	1050	980	
-1.0 m kg	2105 2105	2500 2	2275	1 195	1 115	1 150	1070	
-2.0 m kg	3415 3415	2510 2	2 2 8 0			1 370	1275	
-3.0 m kg		2395 2	2340			1 885	1 820	

#### DIMENSIONS (TRANSPORT)

A	Transport length	6 115 mm
В	Transport width	2220 mm
С	Upperstructure carriage	2040 mm
D	Height over cabin/ROPS	2570 mm
E	Height of Boom – transport	2720 mm
F	Overall length of crawler	2820 mm
G	Tail length	1 800 mm
H	Track gauge	2 195 mm
I	Undercarriage width (blade)	2220 mm
J	Horizontal distance to blade	1 735 mm
K	Blade height	405 mm
L	Track height	680 mm
М	Track pads width	450 mm
N	Min. ground clearance	380 mm
0	Counterweigth clearance	750 mm
P	Engine cover height	1720 mm
Q	Tail swing radius	1 800 mm
R	Center distance of tumblers	1750 mm



#### WORKING AREA

Max. digging reach	6505 mm
Max. digging depth	4 450 mm
Max. digging height	7 390 mm
Max. dumping height	5490 mm
Min. dumping height	2040 mm
Max. vertical digging depth	3840 mm
Overall height over arm by min. swing radius	5560 mm
Arm head distance with work	
equipment retracted as far as possible	1735 mm
Min. swing radius	1940 mm
Max. clearance when blade up	390 mm
Max. depth of blade down	330 mm
	Max. digging depth Max. digging height Max. dumping height Min. dumping height Max. vertical digging depth Overall height over arm by min. swing radius Arm head distance with work equipment retracted as far as possible Min. swing radius Max. clearance when blade up

D

08





## EQUIPMENT



#### **OPERATORS COMFORT / CABINE**

#### Suspension seat Heater Automatic air conditioning C/H\* Radio and speaker Armrests (adjustable) • USB port (music) Wiper AUX 1 on Joystick AUX 2 on Joystick . 8 stored hydraulic settings for attachments Bluetooth interface

#### SAFFTY

••••	
Battery master switch	•
Travel Alarm	•
Warning beacon	•
Lockable hoods	•

#### WORKING EQUIPMENT

Boom and arm load holding valves with overload indicator	•
Double acting circuit for hydraulic quick coupler with piping	•
Breaker&Shear line proportional on Joystick with piping	•
Rotation line proportional on Joystick with piping	•
Flow adjustment for attachments	٠
Dozer blade	٠

#### Always a little bit more

The SANY75C is already fitted with an excellent range of equipment ex-works. Everything is supplied on-board, from the hydraulic quick-hitch already included ex-works as standard, to the extremely robust dozer blade and the Bluetooth interface for using mobile phones.

#### WORKING LIGHTS

ights – front (LED)	•
ights – boom (LED)	•
ights – platform (LED)	•

#### **UNDERCARRIAGE**

Rubber tracks	•
Steel tracks	•
Holes/loops for fixing	•

#### **ENGINE**

Auto idle	•
DPF	•
DOC	•

#### HYDRAULIC SYSTEM

Swing brake	•
2 speed travel	•
Piping for additional hydraulic function AUX 1	•
Piping for additional hydraulic function AUX 2	•
Hydr. Pre-pressure operating joysticks	•

# **A SERVICE YOU CAN RELY ON**

Just as we do with our excavators, we also demand high quality for efficiency, cost-effectiveness and safety. Your SANY dealer is and reliability of our service products. This underlines our happy to help you with a comprehensive range of services to equipment's performance in terms of their durability and their ensure that your machine continues operating efficiently in the excellent price-performance ratio. After all, maintenance is crucial long term.

#### SANY - flexible, fast and always there for you

Rapid assistance, tailored advice and a reliable supply of original parts - that is what we mean by a premium service.

> GERMANY Cologne

#### Standard equipment • Special option

The standard and special options differ depending on the country in which the crawler excavator is delivered. If you have any questions, please contact your dealer directly. \* The air conditioner contains fluorinated greenhouse gases: Refrigerant type: HFC-134a, Global warming potential: 1 430, Quantity: 0.85 kg, CO.,e: 1,22 t

#### Parts supply quick and reliable

With the purchase of a SANY compact excavator you have made an investment in the future. Fast availability of spare parts is your guarantee of minimal downtimes and failure times.



#### Detailed information in black and white

Handbooks and documents are available for all SANY compact excavators, and these can help you with operation, maintenance, servicing and repairs. These include operating and maintenance instructions and technical specifications.

## SANY SERVICE



## HIGHLIGHTS SY75C

# **COMFORT MEETS EFFICIENCY**

The SY75C is one of the most powerful SANY compact excavators and impresses with its robustness and power. The machine can deliver its full performance, whether in road construction or for loading work. With its powerful drive and compact dimensions, this excavator ensures high productivity during everyday work.



The driver's cab impresses with its **ergonomically designed controls**, comfortable driver's seat and outstanding visibility on all sides. It is also optimally sealed off and keeps noise, dust and vibrations away from the driver. In addition, the Bluetooth interface makes it easy for the operator to connect their mobile phone in order to answer calls or play music.

#### **OPTIMAL DESIGN**

With the SY75C, you can get a lot done. And it will remain **robust** and work **powerfully**.

#### **EVERYTHING IN SIGHT**

Perfect visibility on all sides and a rear camera image on a high-resolution display, offering the best views for precise and safe work.

#### **POWERFUL AND CLEAN**

With its **tailored exhaust treatment**, the Yanmar engine achieves **emission standard Stage V** without any difficulty. This means that it is not only environmentally friendly, but also **fuel-efficient.** 

#### ALWAYS OPTIMALLY CONFIGURED

The **sensitive joystick** and clearly arranged **controls** allow machine operators to work safely, confidently and with **minimal force**.

#### DESIGNED FOR MAXIMUM EFFICIENCY

The intelligent **load-sensing hydraulic system** always knows precisely how much hydraulic power is required for each task and delivers precisely the amount of oil needed.

#### **TECHNICAL HIGHLIGHTS**

SANY/

Engine	YANMAR 4TNV98CT
Rated power	42.4 kW / 1 900 rpm
Max. torque	241 Nm / 1 300 rpm
Bucket digging force ISO	53 kN
Swingspeed	10.5 rpm
Mainpump	Variable-piston-pump
Max. oilflow	158 l/min

SY75C



"FOR OUR COMPANY THE PERFECT SOLUTION!" Jens Hansen – EGW Eilderts GmbH

Not all products are available in all markets. As part of our continuous improvement process, we reserve the right to modify specifications and designs without giving prior notice. The figures may contain additional options.



Quality Changes the World

#### **SANY EUROPE GmbH** Sany Allee 1 D-50181 Bedburg fon +49 2272 90531 100 fax +49 2272 90531 109 info@sanyeurope.com www.sanyeurope.com