

7MU202 (B)

5105 KEYLINE GS

FARMotion 45 Stage V engine. Common Rail system. 4 cylinder. 3849 cm³

capacity. Turbo Intercooler. EGR (External Gas Recirculation), DOC

(Diesel Oxidation Catalyst), DPF (Diesel Particulate Filter), SCR

(Selective Catalyst Reduction). 2200 rpm rated speed. Power at rated

speed (ECE R 120): 101 HP / 74 kW. Max

power (ECE R 120): 106 HP / 78

kW. 2 engine memory speed.

Electrohydraulically operated multi-disc oil

immersed Powershuttle and Comfort Clutch button. Electrohydraulically

operated multi-disc oil-immersed PTO

clutch. Lift capacity (without additional ram): 3600 Kg. Electronic battery switch in the cabin.

Without pneumatic trailer brake

Powertrain waterproof sealing

Hand operated park brake

WITHOUT PARKING WEDGE

FULLY HYDROSTATIC INDEPENDENT BRAKING on

all 4 wheels with oil-immersed disc brakes with front logic brake valve (front brakes are excluded with decoupled pedals)

Hydrostatic steering system

Battery: 12V - 100Ah - 900A (EN)

Halogen lights for front and rear

direction indicator and front position light. Rear LED driving lights (position, stop)

Front HALOGEN headlights

Without front work lights on indicators light

Front work lights on bonnet

Without upper headlights

Standard battery electric circuit

Without rear electrical socket for trailer with ABS

Vertical exhaust pipe on cab post

Fuel tank: 145 l / AdBlue tank: 10 l

9" air filter with dust ejectors

Without connection for air-compressor accessories

OPTIONALS:

HC004 Hydraulic Dual Mode trailer braking system (MR)

VF014 Rotary beacon

VG012 4 front + 4 rear work lights on cab roof

VJ024 12V electrical socket + 2 USB + 7-pin socket for equipments (ISO 11786)

5-HL1 HI-LINE cab equipment: includes front and rear rubber floor mat, 2 PTO speeds

GP274 3 rear distributors with flow regulator and quick couplers (3 Float)

XQ007 Hydraulic distributors with Push-pull quick couplers and oil recovery tank

FA100 Front linkage and PTO pre-arrangement

GC056 Cat. II rear lower link arms with automatic couplers (no brand preference)

GF001 Mechanical automatic rear upper link

GT114 Lift assistor rams (4525 kg capacity)

YN001 Swinging drawbar

AA009 Front and rear rubber floor mat cover

AE041 Seat (FABRIC) (air-suspension, adjustable weight and height)

AG003 Passenger seat with seatbelt

VISCOSTATIC cooling fan	
ELECTRONIC engine management	NO003 Front license plate holder
Stage V technology	
Standard Package	TC013 User manual (Danish)
Free hydraulic oil return	
Open centre hydraulic system with constant pump (55 l/min)	RF1283 Tyres: 420/70 R24" front, 480/70R34" rear
Without pre-arrangement for front loader	
Drawbar & hitches (CBM)	WD040 Rear mudguards extension 260 mm (overall width 2200 mm)
Long trailer hitch slider frame	
Rear hitch "CEE" with quick adjustment	
Telescopic stabilizers	WE003 Front steering mudguards
Front clevis	
Without front weight frame	
Mechanical right tie rod and stabilizers	
Mechanical rear lift	
Electronic rear PTO remote control on mudguards	
Hydraulic Powershuttle lever with "Sense Clutch" (adjustable response)	
Standard air filter for cab	
without telematic module	
Electrohydraulic engagement for 4WD and front/rear Differential Lock	
DEUTZ-FAHR GREEN body color	
Without headrest for seat	
Without bracket for external monitor / device	
Cab roof FOPS-compliant (without hatch)	
Manual air conditioning	
Digital display	
Cab accessories: smoking kit, cup holder, smartphone holder	
4 pillars soundproofed Cab with ventilation and heating system, storage areas. Right consolle with mechanical spool valves controls with DETENT mode position	
Telescopic external mirrors	
Rear window wiper	
Rolling safety seat belt	
Radio with Bluetooth, USB, SD card	
Tilting and telescopic steering column	
Cab with fixed front window	
Cab with rear opening window	
Hydro Silent-Block cab/plat suspension	
Fixed PTO shaft	
Without ground speed PTO	

Rear PTO: 540-540E

General specialization for right-hand
drive countries

Standard specs

Homologation for EEC market (MR)

Speed limit sign

Warning plates

Toolbox

Black covers for wheel hubs

Tyres Brand supplied by Factory

Without rear wheel ballast

Front and rear adjustable rims

5 speed gearbox 20F+20R, electrohydraulic

HI-LO

Powershuttle with "STOP & GO" system

Transmission designed for 50 Km/h, limited
to 40 km/h at super-economy engine speed