

6125C RVShift STAGE V  
FARMotion 45 ULTRA. Stage V engine. Common Rail system. 4 cylinder. 3849 cm<sup>3</sup> capacity. VTG Turbo Intercooler. EGR (external Gas Recirculation), DOC (Diesel Oxidation Catalyst), DPF (Diesel Particulate Filter), SCR (Selective Catalyst Reduction). 2200 rpm rated speed. Power at rated speed (ECE R 120): 123 HP / 90,1 kW. Max power (ECE R 120): 129 HP / 95 kW. Max power with BOOST: 136 HP / 100 kW. 1 engine memory speed. Electrohydraulically operated multi-disc oil immersed Powershuttle and Comfort Clutch button. Electrohydraulically operated multi-disc oil immersed PTO clutch. Lift capacity (without additional ram): 5000 Kg. Electronic battery switch in the cabin. Hydraulic Parking Brake (HPB) Powertrain standard sealing Without DUO-MATIC connection WITHOUT PARKING WEDGE Hydrostatic steering system Without pneumatic trailer brake Vertical exhaust pipe on cab post Without engine brake Fuel tank: 160 l / AdBlue tank: 12 l 9" air filter with dust ejectors VISCOSTATIC cooling fan ELECTRONIC engine management Battery: 12V - 100Ah - 1000A (EN) / 650A (IEC) / 560A (DIN) Front headlights for right-hand traffic Without front work lights on indicators light Front work lights on bonnet Without rear electrical socket for trailer with ABS Without electrical socket ISO 11783 Without iMonitor (On-Board Computer) Stage V technology Standard battery electric circuit Front and rear FULL LED driving lights (position, stop and direction lights) Without Connectivity Value Package

#### OPTIONALS:

HEATED mirrors with ELECTRIC adjustment  
AQ025 Manual air conditioning  
AV046 High visibility glass roof hatch with grid sunshade  
DX010 Electrohydraulic engagement for 4WD and front/rear Differential Lock + ASM system  
FA191 FRONT LINKAGE with double acting cylinders (3.000 kg capacity)  
FB002 Front linkage controlled with rear spool valve.  
GN036 1 front (2 outlets) mechanical distributor (diverted from rear outlets)  
GP502 3 rear high flow distributors with flow regulator and quick couplers (3 Float) + 1 electro-hydraulic rear distributor (8 rear outlets) + pre-arrangement for diverted front outlets  
GT116 Lift assistor rams (7000 kg capacity)  
NC059 FRONT SUSPENDED AXLE + FULLY HYDROSTATIC INDEPENDENT BRAKING on all 4 wheels with oil-immersed disc brakes with front logic brake valve (front brakes are excluded with decoupled pedals)  
RA113 Front and rear adjustable WAFFLE rims  
RD117 Ballast for rear wheels (5x5)

Standard Package	total 354 kg)
Less best seller package	
Open centre hydraulic system with constant pump (90 l/min)	RF1578 Tyres: 420/85 R24" (16.9 R24")
Free hydraulic oil return	front, 460/85 R38" (18.4 R38")
Without POWER BEYOND	rear
Without pre-arrangement for front loader	SS011 Mechanical cab suspensions
WITHOUT ACCESSORIES FRONT LIFTING	
Electronic rear lift and PTO remote controls on mudguards	TC013 User manual (Danish)
Cat. III N rear lower link arms with automatic couplers (WALTERSCHEID)	VF017 LED rotary beacon
ELECTRONIC rear lift with AUTO PTO function	VG016 6 front + 6 rear LED work lights on cab roof
Mechanical right tie rod and stabilizers	
Without front PTO	VJ031 12V electrical socket + USB sockets + 7-pin socket for equipments (ISO 11786)
Without front weight frame	
Rear hitch "CEE" with quick adjustment	
Long trailer hitch slider frame	
Mechanical automatic rear upper link	WD040 Rear mudguards extension 260 mm (overall width 2200 mm)
Without Application Package Basic	
Tilting and telescopic steering column	
Rolling safety seat belt	WE003 Front steering mudguards
Rear window wiper	
TopVisionPro 4 pillars soundproofed Cab, RVSHIFT satellite armrest. Ventilation and heating system, electronic battery switch.	YE000 Without front clevis
Right consolle with mechanical spool valves controls with DETENT mode position.	YG009 Self-locking automatic stabilizers
Left consolle with upper flat storage area and PTO selector levers operated with bowden cables	YS002 Drawbar & hitches (SAUERMANN)
InfoCentrePro with 5" colour display (km/h)	AX001 Cab floor mat cover
Headrest for seat	VQ003 2 upper LED headlights on cab post
DEUTZ-FAHR GREEN body color	
Without GNSS receiver	HC004 Hydraulic Dual Mode trailer braking system (MR)
Without automatic steering system	
Standard air filter for cab	
Hydraulic Powershuttle lever with "Sense Clutch" (adjustable response)	YN001 Swinging drawbar
Removable PTO shaft	
Without ground speed PTO	AO002 RVSHIFT ADVANCED satellite armrest with joystick for the control of: transmission, hand throttle, engine memory speed, rear lift and PTO. ADVANCED functions: 3 programmable jolly buttons for flexible use of the
Rear PTO: 540-540E-1000	
Cab with fixed front window	
Cab with rear opening window	
Without iMonitor support	
BTM - Basic Telematic Module	

Without cab accessories  
Without cooling box  
Without specialization  
Standard specs  
Homologation for EEC market (MR)  
Speed limit sign  
Warning plates  
Toolbox  
Transmission designed for 50 Km/h, limited to 40 km/h at super-economy engine speed  
Powershuttle with ADVANCED "STOP & GO" system  
RVSHIFT transmission. 20+16  
full-powershift concept. Automatic PowerShift (APS) function. Cruise control. 2 setting modes (Work / Transport) fully customizable. Automatic management of Normal and Heavy Duty ranges  
Black covers for wheel hubs  
Tyres Brand supplied by Factory

most common functions, comfort thumbwheel for cruise speed adjustment and a total of 2 engine memory speed buttons

REF. (P)1101/(S)1101

S/N: ZKDLW702W0TD50006

Engine N.: 246267