

## **SY215E**


**Engine power** 

150kW/1800rpm

Bucket capacity
1.1m³

Operating weight

23200kg





http://www.sanyglobal.com

This manual was printed in 2023. The product information may have been changed when you read it. Products (including specific configuration, detail, etc.) are based on the specific models and products applicable to markets outside China, which are displayed and sold by agents. For more details, please visit the local authorized agent of SANY Heavy Machinery Ltd.





# The core configuration is energy efficient



#### High power motor

The customized permanent magnet synchronous motor has the advantages of high power density, high torque density, high efficiency, safety and reliability, and low energy consumption.



#### **High Performance Battery**

The 422KWh high-performance lithium-ion battery has the advantages of high power density, high protection level, long battery life, short charging time, safe and reliable, intelligent fault diagnosis and so on.International first-class brand lithium ion standard battery pack, more than 10 years of designed service life, a charge can comprehensive battery life of 6-10h.



#### **Integrated Type Controller**

Configuration of customized multi-one inherited controller, using a high degree of circuit integration to achieve the electric drive MCU function, three-phase AC charging OBC function, low-voltage power supply DC/DC function, vehicle control VCU function, at the same time with the power precharge auxiliary function, small size, high integration.



#### Main pump

With K7V125 main pump, using the new fourth generation hydraulic system (electronic positive flow system), displacement in the same tonnage of products in the performance, more compliant, sensitive, better coordination.



#### Main valve

Sany main valve adopts Kawasaki developed products, new additions of the middle oil circuit cut-off, bucket rod 2 valve core electronic control and other functions, low pressure loss, low energy consumption.



QUALITY CHANGES THE WORLD QUALITY CHANGES THE WORLD

## Advanced energy saving technology

#### Dynamic optimization intelligent control system

Equipped with fully electronically controlled "positive flow" system and SANY's self-developed "DOMCS" motor-hydraulic pump-main valve integrated dynamic optimization intelligent control system, follow up the optimal output power required by the load.

Efficiency improvement 8%. Energy consumption reduction 10%.

#### **AOCT self-optimizing control technology**

Equipped with multi-stage high-power electric control fan, intelligent speed control, hydraulic oil radiator - electronic coolant radiator independent arrangement, independent temperature control - thermal management controller, motor electric control using series circulation liquid cooling system to ensure heat dissipation efficiency.

Energy consumption reduction 30%. Noise reduction 20%.





#### Advanced machine control system

The main spool is fully electronically controlled The main valve spool is all electrically controlled, the control is more flexible, and the human-machine interaction is more friendly.

High performance controller Match high-performance controller and optimize control algorithm.

System security protection Add safety functions such as abnormal alarm/emergency stop/start diagnosis/redundancy control when the system is abnormal to ensure man-machine safety.


#### Smart and convenient charging



Standard with 2 national standard charging ports Supports DC fast charging



Intelligent monitoring of charging status Optional high-power split type, Integrated DC quick filling pile Charging time ≤1.5 hours




### Maintenance and service









#### Convenient maintenance

The large-area covering piece is opened. After opening, it can stand on the ground for daily maintenance and maintenance, which is convenient for maintenance and good accessibility. For harsh working conditions, strengthen the convenient design of maintenance parts replacement, "large space, easy to start", and increase the operating space of various maintenance parts replacement by 20%-30%.

Radiator: The external protection network is specially designed, the dirt is blocked in the outerside of the protection network, just remove the protection network to clean.

#### Worry free after sale

The national agents and the world's five regional agents provide a strong guarantee for Sany's after-sales service, "5231", "110", "111" commitment for the global service.



Service 4.0 "5231" life without worry



Service "110" **Satisfactory China Tour** 



Service "111" Comprehensive and thoughtful



arts can save up to 50%

24 hours troubleshooting,

12 hours compensation desk shift

Micro digging, small digging machine provides 1 year /3000 hours warranty.

Over 19 tons of large excavator extended warranty to 3 years /7000 hours.



Customer problems at the touch of a button



Advanced equipment: Single equipment service resources, higher than the industry standard.





As long as you APP a key call, I will do it all.





One to one exclusive Honor service: Special service, exclusive honor.



Micro dig, small dig: send 7 free spot check within 10000 hours. Medium dig: send 9 free spot checks within 10000 hours. Big Dig: 11 free spot checks within 10,000 hours.

after signing a special agreement

#### e-Visun

Sany excavator is equipped with self-developed "Yiwei Xun" system to build an intelligent construction management system and lower management costs. The mobile phone can be controlled with one key through the e-visun APP, check the machine status, and book various services online.











11 12

# Production research and development system





### Advanced manufacturing technology

Advanced manufacturing technology is a reliable guarantee for creating excellent products. Sany has RGV assembly line and automatic welding robot, with high precision machining equipment and precision machining center.



#### Complete R & D test system

Complete R & D test system is a strong backing for excellent performance. Complete machine durability test center, each excavator must experience more than 1500 hours of field excavation test.

The working device, cab, hydraulic components and other heavy components must undergo more than 300,000 fatigue tests.




#### Safety certification


Advanced profile skeleton design, fully meet the European standard ROPS safety requirements after 30h high strength bench vibration test safe and sound


## **Technical specification**

Specification	SY215E	Overall size(mm) SY215E
Machine weight	23200 kg	A.Overall length 9910
Bucket capacity	1.1(0.8-1.2) m <sup>3</sup>	B.Overall width 2980
Rated storage energy	422 kWh	C.Total height 3440
Integrated battery life	6-10 h	D.Upper width 2875
motor s	Permanent magnet ynchronous AC motor	E.Total height (top of cab) 3075
Rated power	150 kW/ 1800 rpm	F.Standard track plate width 600
Travel speed (high/low)	) 5.4/3.3 (km/h)	G.gauge 2380
Turning speed	12.5 rpm	H.Minimum ground clearance 440
Tractive effort	220 kN	I.Tail radius 3125
Climbing ability	70%(35°)	J.Track grounding length 3445
Bucket digging force	138 kN	K.Track length 4250
Bucket rod digging force	e 103 kN	

Operating range (mm)	SY215E
a.Maximum excavation height	9600
b.Maximum unloading height	6730
c.Maximum digging depth	6255
d.Maximum digging distance	10280
e.Minimum radius of turn	3730
f.Maximum height at minimum turning radius	7680







more than 300,000 fatigue tests.

## Standard configuration

Three-current syst	em	Cab		Lower walking body
Lithium-ion battery pack	•	Soundproof steel cab	•	Walking motor guard plate
Permanent magnet synchronous motor	•	Reinforced light glazing	•	Track guide mechanism •
Integrated controller	•	Silicone oil rubber shock absorber	•	Track tightening mechanism •
Battery self-heating	•	Open roof, front wall upper Windows and doors	•	Driving wheel •
High voltage interlock	•	Rear window emergency exit	•	Sprocket and support wheel
Insulation testing	•	Wiper with cleaner (silent)	•	Reinforced chain rail •
Intelligent fault diagnosis	•	Hover seat with adjustable armrests and adjustable reclining	•	600mm three-rib track plate •
Standard charging interface	•	AM-FM radio with digital clock (complimentary)	•	Bottom cover plate •
Dc charging pile	0	Footrest, floor mat	•	
		Speaker, rearview mirror	•	
		Safety belt, fire extinguisher (complimentary)	•	
		Drinking cup holder, car light	•	
		Escape hammer	•	
		Storage bins, sundries bags	•	
		Pilot control cut-out lever	•	
		Fully automatic air conditioner	•	
		Sun shade	•	
		One click to start the machine	•	
		10 "smart touch screen	•	
		Bluetooth	•	
		Multifunction panel	•	
		Front guard net	0	

#### • According to the standard o Said matching

## Standard configuration

Hydraulic system		Front-end working device		Upper revolving platfor
Working mode selection switch	•	Flange pin	•	Hydraulic oil level gauge
Control valve with main relief valve	•	Welded bucket	•	Rotary parking brake
Control valve with spare oil port	•	Welded connecting rod	•	Rear view mirror (right)
Oil suction filter	•	Integrated lubrication system	•	
Return filter	•	All bucket pins are equipped with dust-proof seals	•	
Pilot filter	•	Reinforced all welded box boom	•	
		Reinforced all welded box bucket rod	•	
Air conditioning system				
Heating and cooling (imported high-grade)				
Heating and cooling (imported high-grade)	•			
Heating and cooling (imported high-grade) Integrated air conditioning control panel				
Heating and cooling (imported high-grade) Integrated air conditioning control panel	•			
Heating and cooling (imported high-grade) Integrated air conditioning control panel Fresh air intake system	•			
Heating and cooling (imported high-grade)  Integrated air conditioning control panel  Fresh air intake system  other	•			
Heating and cooling (imported high-grade)  Integrated air conditioning control panel  Fresh air intake system  other  Standard battery	•			
Heating and cooling (imported high-grade)  Integrated air conditioning control panel  Fresh air intake system  Other  Standard battery  Lockable top cover	•			
Air conditioning system  Heating and cooling (imported high-grade)  Integrated air conditioning control panel  Fresh air intake system  Other  Standard battery  Lockable top cover  Non-slip stickers, handrails and sidewalks  Walking direction marker on the walking frame	•			

16

15

Hand grease gun

